



RightUnits IO

[SPECIFICATIONS +](#)

[SOFTWARE & DOCUMENTATION +](#)



Specifications

Supply voltage	24VAC/DC, 50Hz
Power consumption	5W for the base module
Temperature*	Storage (-40 °C to +85 °C) / Operating (-20°C to +70 °C)
Humidity	Max. 95% RH non-condensing
IP Class	IP2x (Without enclosure)
Mounting	DIN rail
Serial Ports	1x RS485
TCP Ports	TCP/ IP port (10Base-T/100Base), Optional Gigabit
USB Ports	USB port for interface

Additional Modules

Part Number	Modules
RB 4.x1	Rs485 - for any serial communication (set of 2)
RB 4.x2	RS232 - for serial and optical communication
RB 4.x3	Ethernet 10/100 Base T (set of 4); Gigabit Ethernet optional
RB 4.x4	Universal Serial Bus
RB 4.x5	CAN Bus
RB 4.x6	4x Analog Input
RB 4.x7	4x Analog Input




RB 4.x8	8x Analog Input
RB 4.x9	8x Analog Output
RB 4.x10	8x Digital Input
RB 4.x11	8x Digital Output
RB 4.x12	4/4 Hybrid Analog IOS
RB 4.x13	4/4 Hybrid Digital IOS

Software & documentation

Product sheet

 [RightUnits IO](#)



Seamless operations | Delighted customers

- 📍 DMRC-D21 Corporate park Dwarka, New Delhi
- 📍 Shell Technology Center KIADB Industrial Park Bengaluru, Karnataka
- ✉ connect@rightwatts.com
- ☎ +91-11-41635826
Weekdays 9 AM - 6 PM

© 2018 RIGHTWATTS | ALL RIGHTS RESERVED

Quick Links

- [Home](#)
- [Try RightWatts](#)
- [Careers](#)
- [Contact Us](#)

Our Newsletter

Sign Up to our Newsletter to get the latest news and offers.

Your email address

[SUBSCRIBE](#)

Enter Your Email Address*

[in](#) [▶](#)

